

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
30 August 2001 (30.08.2001)

PCT

(10) International Publication Number  
**WO 01/63337 A1**

(51) International Patent Classification<sup>7</sup>: **G02B 26/02**

(21) International Application Number: **PCT/CH01/00118**

(22) International Filing Date: 23 February 2001 (23.02.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
00810162.8 25 February 2000 (25.02.2000) EP

(71) Applicant (for all designated States except US): **CSEM  
CENTRE SUISSE D'ELECTRONIQUE ET DE  
MICROTECHNIQUE SA** [CH/CH]; Jaquet Droz 1,  
CH-2007 Neuchâtel (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BOURGEOIS,**

**Claude** [CH/CH]; Ministre 18, CH-2014 Bôle (CH). **DE-  
BERGH, Patrick** [BE/CH]; Rue des Prélards 13, CH-2088  
Cressier (CH). **GONSETH, Stephan** [CH/CH]; Ch. des  
Croisettes 7, CH-1066 Epalinges (CH). **PERREGAUX,**  
**Grégoire** [CH/CH]; Bourguillards 10, CH-2072 St-Blaise  
(CH). **RUDOLF, Felix** [CH/CH]; Ch. du Cudeau-du-Haut  
25, CH-2035 Corcelles (CH). **VAN DER WIEL, Appolo-**  
**nus** [NL/CH]; Rue de l'Orée 104, CH-2000 Neuchâtel  
(CH).


(74) Agent: **GRESSET-LAESSER-NITHARDT**; Cabinet  
de Conseils en Propriété Industrielle, Puits-Godet 8A,  
CH-2000 Neuchâtel (CH).

(81) Designated State (national): US.

(84) Designated States (regional): European patent (AT, BE,  
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,  
NL, PT, SE, TR).

[Continued on next page]

(54) Title: SWITCHING DEVICE, PARTICULARLY FOR OPTICAL SWITCHING



(57) Abstract: This switching device comprises at least one cell made up of a moving structure consisting in a flexible cantilever beam (14) and an integral screen (16) attached to said beam, being able to move between two end positions (A, B) and of actuating electrodes (20) for subjecting said structure to forces of attraction to control its movements. The electrodes (20) are located on each side of the beam (14) in such a way as to follow its exact shape when it is in one of its two end positions. A regular movement of the moving structure and a reliable operating of the switching device are thus obtained. This invention may be used in optical switching applications.

WO 01/63337 A1

WO 01/63337 A1



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*